




KRS Guide Wheel Bearing Co., Ltd



25,000 mm x 62,000 mm x 17,000 mm NTN
N305 cylindrical roller bearings

Bearing No. N305

N305 Bearing 2D drawings and 3D CAD models

Size	25x62x17 mm
Bore Diameter	25,000 mm
Outer Diameter	62,000 mm
Width	17,000 mm
d	25,000 mm
D	62,000 mm
B	17,000 mm
C	17,000 mm
Category	Cylindrical Roller Bearings
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.23
EAN	4547359151213
Product Group	B04144
Bore Profile	Straight
Cage Material	Steel
Precision Class	RBEC 1 ISO P0
Number of Rows of Rollers	Single Row
Separable	Outer Ring - Both Sides
Rolling Element	Cylindrical Roller Bearing
Profile	Complete with Outer and Inner Ring
Snap Ring	No
Internal Clearance	C0-Medium
Retainer	Yes



KRS Guide Wheel Bearing Co., Ltd

Relubricatable	Yes
Inch - Metric	Metric
Other Features	2 Rib Inner Ring Plain Outer Ring Cage On Inner Ring OD
Long Description	25MM Bore; Straight Bore Profile; 62MM Outside Diameter; 17MM Width; Steel Cage Material; RBEC 1 ISO P0; Single Row; Outer Ring - Both Sides Separable; No Snap Ring; Relubricatable; C0-Medium Inter
Category	Cylindrical Roller Bearing
UNSPSC	31171547
Harmonized Tariff Code	8482.50.00.00
Noun	Bearing
Manufacturer URL	http://www.ntnamerica.com
Manufacturer Item Number	N305
Weight / LBS	0.508
Outside Diameter	2.441 Inch 62 Millimeter
Width	0.669 Inch 17 Millimeter
Bore	0.984 Inch 25 Millimeter
bore diameter:	25 mm
precision rating:	ISO Class 0
outside diameter:	62 mm
maximum rpm:	14000 rpm
overall width:	17 mm
bearing material:	Hardened Alloy Steel
flanges:	(2) Inner Ring
cage material:	Pressed Steel
bore type:	Straight
finish/coating:	Uncoated
number of rows:	1



KRS Guide Wheel Bearing Co., Ltd

closure type:	Open
internal clearance:	CN
outer ring width:	17 mm
ring separation:	Separable Outer Ring
fillet radius:	1 mm
operating temperature range:	-40 to 120 ° C
series:	N
dynamic load capacity:	41500 N
manufacturer product page:	Click here
static load capacity:	37500 N