



# KRS Guide Wheel Bearing Co., Ltd



85,000 mm x 130,000 mm x 22,000 mm NTN  
6017ZZNR deep groove ball bearings

Bearing No. 6017ZZNR

6017ZZNR Bearing 2D drawings and 3D CAD models

Size	85x130x22 mm
Bore Diameter	85,000 mm
Outer Diameter	130,000 mm
Width	22,000 mm
d	85,000 mm
D	130,000 mm
B	22,000 mm
C	22,000 mm
Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.889
Product Group	B00308
Enclosure	2 Metal Shields
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	Yes
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch - Metric	Metric
Long Description	85MM Bore; 130MM Outside Diameter; 22MM



## KRS Guide Wheel Bearing Co., Ltd

	Outer Race Diameter; 2 Metal Shields; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; Yes Snap Ring; No Internal Special Features
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	<a href="http://www.ntnamerica.com">http://www.ntnamerica.com</a>
Manufacturer Item Number	6017ZZNR/2A
Weight / LBS	1.96
Outer Race Width	0.866 Inch   22 Millimeter
Outside Diameter	5.118 Inch   130 Millimeter
Bore	3.346 Inch   85 Millimeter
bore diameter:	85 mm
precision rating:	ISO Class 0
outside diameter:	130 mm
finish/coating:	Uncoated
overall width:	22 mm
bearing material:	High Carbon Chrome Steel
bore type:	Round
cage material:	Steel
closure type:	Double Shielded
inner ring width:	22 mm
row type & fill slot:	Single Row Non-Fill Slot
outer ring width:	22 mm
snap ring included:	With Snap Ring
maximum rpm (grease):	5000 rpm
internal clearance:	CN
fillet radius:	1.1 mm
operating temperature	-40 to 120 ° C



## KRS Guide Wheel Bearing Co., Ltd

range:	
maximum rpm:	5900 RPM
dynamic load capacity:	49500 N
series:	60
static load capacity:	43000 N
manufacturer product page:	<a href="#">Click here</a>